



3501 East La Palma Avenue - Anaheim, California 92806

Ph: 714-666-0108 and 714-666-0109

Fax: 714-666-0110

www.weisrobart.com

WEIS/ROBART STAINLESS STEEL TOILET PARTITIONS

CARE & MAINTENANCE INSTRUCTIONS

How to keep your Weis/Robart Stainless Steel toilet partitions beautiful for many years

Weis/Robart Stainless Steel toilet partitions care and maintenance instructions to help you take care of them properly, because just as in any other room of your building, your toilet partitions are exposed to use and atmospheric conditions that will require cleaning from time to time.

GRAFFITI & DIRT

The following methods of cleaning can be used to keep your Weis/Robart stainless steel toilet partitions always looking their best:

- Use a clean, damp, non-abrasive cotton cloth to wipe down all surfaces. For routine maintenance use a soft sponge with a detergent and water solution or ammonia, rinse and wipe dry. It is important to use cleaners without abrasives such as Luster Sheen Stainless Steel cleaner.
- It is best for stubborn marks and vandalism to use a cleaner such as Bug and Tar and follow with a touch up of stainless steel cleaner.
- Never allow caustic cleaners containing acids such as toilet bowl or tile cleaners to come in contact with the stainless steel finish. If caustic cleaners come in contact with the stainless steel finish, severe discoloring that is impossible to remove will occur.

CUTS & SCRATCHES

You can mend scratches by using a Scotch-Brite pad/brush in the same direction as the grain.

Upon completing any repairs for your partitions, spray the surface of your panels and/or doors with a stainless steel cleaner and use a clean, damp, non-abrasive cotton cloth to wipe down all surfaces to give your Weis/Stainless Steel product back its original bright and shiny finish –

Just like new again.

HARDWARE MAINTENANCE

Use a clean, damp, non-abrasive cotton cloth to wipe down all surfaces. Do not use any abrasives cleaning agents on any of the partitions and/or partition hardware.

All hanger bolts, brackets, hinges, latches and other fastening devices should be checked at least twice per year. It is important to check your partition hardware so that you can replace or tighten all loose or broken items at once.

Avoid using steel wool, and any products containing harmful acids such as muriatic, phosphoric and hydrochloric that can discolor and destroy your stainless steel partitions.

*Use of brand names is intended only to indicate a specific type of cleaner. This information does not constitute an endorsement, nor does the omission of any brand name cleaner imply its inadequacy. Many of these types of products can be found in local supermarkets, department and hardware stores. Before each use, follow the directions listed on the commercial cleaner of your choice.